

TELFORD 30



Built according to a distinctive hybrid design philosophy, the Telford 30 is a multipurpose DP3 vessel suitable for offshore accommodation, hook up and construction activities. The Telford 30 vessel has a large unobstructed main deck, a 270mt crane and large-scale accommodation capacity.



Accommodation & Hook Up



Offshore Construction



Telford Offshore International Ltd, Mazaya Business Avenue, Building AA1, 10th Floor, Office 1005, P.O. Box 337673, Jumeirah Lakes Towers, Dubai, United Arab Emirates



tenders@telfordoffshore.com



www.telfordoffshore.com



+971 4 575 5061



All information, data and other technical description in this document are for guidance purposes only and subject to change. © April 2018 – Telford Offshore ® is a registered UK trade mark – All rights reserved.

SPECIFICATIONS

General

Classification ABS, ₩A1, Barge,

♣DPS-3, **♣PAS**, CRC

Flag Gibraltar Call Sign ZDHS6 9420655 **IMO Number** Delivery October 2007

Principal Dimensions

Length Overall 111 00 m Breadth 30.48 m **Extreme Breadth** 38.00 m Depth Main Deck 6.71 m Operating Draft 4.719 m **Maximum Draft** 7.719 m (Retractable thruster deployed) **Gross Tonnage** 13340 t

Accommodation

Net Tonnage

Fully air-conditioned permanent accommodation for up to 500 persons in cabins all with individual bathroom facilities. Including conference room, offices, cinema, gymnasium, recreation rooms, laundry, internet café as well as a hospital.

4002 t

500 berths in 133 cabins

2 x 1 person cabins 13 x 2 persons cabins 118 x 4 persons cabins

DP System

Kongsberg K POS 21

Aft Working Bridge

Kongsberg

Fore Navigation Bridge

K POS 11

Power Plant

Main Generators (Caterpillar)

3 x Diesel Engines type CAT 3516 B (1825 kW)

Main Deck

Deck Area

700 m Approx. Main Deck Top of Firing line 268 m² Total 551 m² Sheltered area 289 m² inside Conveyor house

Deck Strength 10t/ m²

Gangway

Electric-Hydraulic Telescopic Personnel Transfer Gangway (Uptime/Marine Aluminium) 36.50 m Operational length

Cranage

Mast Crane (Seatrax)

Main Hoist STX 270mt@12m Aux. Hoist STX-man-riding Capacity 25mt@57.3 m

Pedestal Crane (TTS Marine)

Main Hoist 34 mt @20 m

22 mt @30 m

Aux. Hoist (not man-riding)

5mt@31 m

Propulsion

Bow Thruster

1 x electrically driven 1355kW

Forward/Aft Thruster 4 x fixed pitch hinged azimuth

(Thrustmaster)

hydraulic driven thrusters type

OD1500 (1200kW)

(Wartsila)

Center Aft Thruster 1 x electrically driven retractable

fixed pitch thruster (1000kW)

Cargo Capacities

Dead Weight 7396.08 t Fuel Oil 2169.60 m³ Lube Oil 97.30 m³ 2429.80 m³ Fresh Water 4950 2 m³ Ballast Water

Radio/Communication

V-Sat Antenna (Intellian V150NX)

GMDSS Areas 1,2 & 3

EPIRB

SART

Integrated Telephone System **Sound Powered Telephone Public Address System**

DP Reference System

1 x RADius 2000 (dual interrogators)

2 x DGPS Receivers (DPSi2 + DPSi4)

3 x Gyro Compass

3 x Motion Reference Units

1 x Lightweight Tautwire

1 x Gangway (if connected)

1 x Cyscan + Prisms Clusters

3 x Wind Sensors

Helideck

ABS, CAP437 9th Edition compliant suitable for Sikorsky S-92A Helibus

Max. "D" 22.20m Max. T.O.W. 13t

Helideck Monitoring System 300

Fixed Foam System (3 monitors)

Endurance

Fresh Water 2 x45m3/24hrs

1x65m3/24hrs

Fuel Oil (typical)

5m³/24hrs Harbor

20m³/24hrs Transit

(24m3/24hrs (80% load) 5x Thrusters in use 15m3/24hrs (50% load) 4x Side thrusters in use

DP 15m³/24hrs

Lifesaving Appliances

Liferafts 60 x 25 persons **Fast Rescue Boat** 1 x 6 persons

