

TELFORD 30









Built according to a distinctive hybrid design philosophy, the Telford 30 is a multipurpose DP3 vessel suitable for rigid pipelay, offshore construction and accommodation and hook up activities. The Telford 30 vessel has a large unobstructed main deck, a 270mt crane and large-scale accommodation capacity. The T30 has been utilized on major projects offshore West Africa delivering accommodation services with platform supply capability to support construction and operations in Block 15 on Kizomba A, offshore Angola, and Chevron to serve the Agbami FPSO, offshore Nigeria, where her accommodation capacity was increased with a Portable Accommodation Block (PAB) installed on the main deck. As a pipelay vessel she was awarded* by NPDC, a subsidiary of Nigerian National Petroleum Corporation (NNPC), the installation and commissioning of a new 16" x 13.5 km pipeline in OML 119, offshore Nigeria. The pipeline was designed to allow for both routine and intelligent pigging, with a pig launcher on Okpoho platform and the pig receiver on FPSO Mystras at the Okono field.

*Project executed by West African Ventures

SPECIFICATIONS

General

IMO Number

• Classification ABS № A1 Barge (E), № PAS, № DPS-3, CRC

Flag GibraltarCall Sign ZDHS6

• **Delivery** October 2006

9420655

Principal dimensions

• Length Overall 111.08m

• Breadth 30.48m

• Extreme Breadth 38.00m

• Depth Main Deck 6.71m

• Operational Draft 4.70m

• Maximum Draft 5.00m

• Maximum Draft 7.70m

(Retractable thrusters deployed)

• Gross Tonnage 12 020t

• Net Tonnage 3606t

Cranage

• Mast Crane (Seatrax)

- Main Hoist 270mt @16m- Aux. Hoist 27mt @12.2m

• Pedestal Crane (TTS Marine)

- Main Hoist 34mt @ 20m

22mt @ 30m

- Aux. Hoist (man-riding)

5mt @ 31m

Clear Deck Area

• Approx. 700m²

Deck load

• 10t/m²

Capacities

- Fuel Oil (storage) 2040m³
- Fuel Day (day tank) 47m³
- Fuel Oil Purification 64m3
- Fuel Oil Settling 64m³

- Lube Oil 90m³
- Fresh Water 3111m³
- Ballast Water 6362m³
- Sludge Oil 41m³
- Dirty Oil 46m³
- Black/Grey Water 473m³
- Bilge Water 160m³

Service Air

• Service Air Compressor (Deno) 2x24m³/min FAD@6 bar

DP System

- Kongsberg Simrad SDP 21
 Aft Working Bridge
- Kongsberg Simrad SDP 11 Fore Navigation Bridge

DP Reference System

- 1x Radius 1000 (independent operated)
- 2xDGPS Receivers
- 3x Gyro Compass

- 3x Motion Reference Units
- 1x Lightweight Tautwire
- 1x Gangway (if connected)
- 1x Cyscan + Prisms Clusters
- 3x Wind Sensors

Power Plant

Main Generators (Caterpillar)
 3 x diesel engines CAT 3 516 B
 (1 825kW)

Propulsion

- Bow Thruster (Wartsila)
 1x electrically driven 13 55kW
- Forward/Aft Thrusters
 (Thrustmaster)
 4xfixed pitch hinged azimuth
 hydraulic driven thrusters type

OD1500 (1200kW)

Center Aft Thruster (Wartsila)
 1x electrically driven retractable fixed pitch thruster (1000kW)





Endurance

• Fresh Water 3x50t/24hrs

• Fuel Oil (typical)

- Harbor 5m³/24hrs - Transit 20m³/24hrs (2 x aft thrusters only)

- DP 13m³/24hrs

Helideck

- ABS, CAP437 compliant, suitable for Sikorsky S-92A Helibus
- Max. "D" 22.20m
- Max. T.O.W. 13t
- Helideck Monitoring System 100
- Fixed foam system (3 monitors)

Accommodation

- Fully air-conditioned permanent accommodation for up to 296 persons in cabins all with individual bathroom facilities.
 Including conference room, offices, cinema, gymnasium, recreation rooms, laundry, internet café as well as an hospital.
- 96 berths in 77 cabins
 - 2x1 person cabins
 - 3x2 persons cabins
 - 72 x 4 persons cabins

Radio/Communication

- V-Sat Antenna (Intellian)
- GMDSS Area 1,2 & 3
- EPIRB
- SART
- Integrated Telephone System
- Sound Powered Telephone
- Public Address System

Lifesaving appliances

- **Liferafts** 36 x 25 persons
- Fast Rescue Boat 1x6 persons

Gangway

 Electric-Hydraulic Telescopic Personnel Transfer Gangway (Marine Aluminium)
 Operational length 36.50m

Pipelay equipment

- Pipelay System (SAS)
 Starboard mounted single joint
 S-lay system under dismountable
 Firing Line shelter
- Capacity
 4"-48" diameter pipe (with coating 60")
- Tensioners
 1x100t Horizontal Tensioner
- Davits
 5x60t with load cells
- Stinger Length 35m, supported by stuts
- Workstations
 5 working stations for welding,
 NDE (X-ray or Ultrasonic), pipe
 repair and coating
- A&R system (Rolls Royce)
- 100t A&R Winch 100t
- 100t A&R Measuring Sheave

Mooring System

10 point Mooring System (PH)
 4x110t Single drum winches,
 hydraulic driven, with 1500m of
 Ø52mm Steel Wire Rope capacity
 4x150t Single drum winches,
 hydraulic driven with 2000m of
 Ø63mm Steel Wire Rope capacity


- 2 single drum winches (Rolls Royce), hydraulic driven Type 100t, 64mm wire, 1800m in 14 layers
- Capstan (Mentrade) 4x10t

Additional Data

- Sewage Treatment Unit (Hamworthy)
 1 unit, with nil overboard discharge
- Incinerator (TeamTec) 1x800,000kcal/h
- Yokohama Fenders 6.50×3.30m



LOCATIONS - OPERATIONS



Our locations around the world mean we're always close to our customers. We serve all operators, from majors, internationals and NOCs to small independents and contractors so let's keep in touch.

Latin America

Mexico

Calle 35 D, Suite 10 Col Malibran, 24197 Cuidad del Carmen, Campeche Mexico

Tel: +52 (1) 5564 151 719 (Mexico) +54 (9) 11 2790 2463 (Argentina)

Europe

The Netherlands

Maxwellstraat 2 3316 GP Dordrecht The Netherlands Tel: +31 78 6526 930

Tel: +233 203 654 079

West Africa

Angola

Condominio Mares do Sul Casa no. A07 Talatona - Benfica Luanda Angola Tel: +244 923 522175

Ghana

F181/5 Josiah Tongorara Street PMB CT 68 Cantonments Accra, Ghana

+233 544 312 460

Middle East

UAE, Dubai - Headquarters

Telford Offshore Ltd Floor 31, Reef Tower P.O. Box 5003365 Jumeirah Lakes Towers Dubai, United Arab Emirates Tel: +971 4 350 7600

Asia-Pacific

Australia

Level 24, 77 St Georges Terrace Perth WA 6000 Australia

Tel: +61 8 9218 5888

contact@telfordoffshore.com

All information, data and other technical description in this document are for guidance purposes only and subject to change. @ April 2018 - TELFORD OFFSHORE* is a registered UK trade mark - All rights reserved.

CBMS-TOL-MKT-BRO-003 RO